



MASSEY FERGUSON

Model #

MSRP

\$ 136,312.00

- MF 5M.115 Dyna-4 Cab
- 5M.115 Cab Dyna-4
- 3rd Mech Baseline Valves
- F380/85R24 R1 / R460/85R34 R
- OptiRide Passive Susp.
- LED Handrail Worklights
- LED Roof Worklights
- Live 3rd Loader Prov.
- 83" Euro Bucket - General
- Wgt Adapter Pkg-2x50kg adp w
- Wgt Pkg-2x50kg wts (stackabl
- FL3723 LL110-live3rd

Total Retail Price

\$ 136,312.00

Prepared for:

Good Through: 07-31-2026

Dealer Representative: Dillon Robinson

Representative Email: jlrob10@gmail.com

Representative Phone:

Lowest Payment

\$1,495.00/Month

Cash Price

\$109,398.00

RECEIVED

JUL 30 2026

NAVARRO COUNTY
AUDITOR'S OFFICE

Low Rate

Finance Low Rate

Sale Price	\$ 109,398.00
Down Payment + Trade-In:	\$ 0.00
Net Price	\$ 109,398.00
+Taxes and Fees	\$ 0.00
Amount Financed	\$ 109,398.00

Financing Options*

0.00% for 36 months
0.00% for 48 months
1.99% for 60 months
3.24% for 72 months
3.99% for 84 months

Monthly Payment

\$ 3,039.00
\$ 2,279.00
\$ 1,917.00
\$ 1,674.00
\$ 1,495.00

2
YEARComprehensive
Warranty

Cash Price

Cash Price

Sale Price	\$ 109,398.00
Trade-In:	\$ 0.00
Net Price	\$ 109,398.00
Taxes	\$ 0.00
Final Customer Price	\$ 109,398.00

ASK ABOUT
EXTENDED
COVERAGE

Notes

This price has the loader removed

This Letter is a non-binding indication of interest regarding a possible transaction on the general terms and conditions outlined herein and is not a legal commitment. This Letter is intended for the use of the Customer only. *The following is a proposal for financing for the customer named herein ("Customer") regarding the equipment described herein ("Equipment") by AGCO Finance LLC for discussion purposes only. Customer participation subject to credit qualification and approval by AGCO Finance LLC. Not all Customers may qualify for this rate or term. This proposal is not a statement of all terms and conditions of any financing that may be approved. This Letter is intended for the use of the Customer only. This Letter is valid until "Good Through" date listed above and thereafter shall automatically be deemed to be null and void. ***The cash price is a good faith dealer estimate only. See dealer for details.


AGCO
Your Agriculture Company

Model Number: MF5M.115D
Model Year: 2026

QQ Number: QQ-1063147
Serial Number: AGCMH060ATB019001

Invoice Number: 92346777
Order Number: 1986565

Dealership Name: Pomeroy Ranch Equipment LLC
Location: Kerens (630525)



MASSEY FERGUSON

5M Series

(F.O.B. PORT OF ENTRY)

PLATFORM EDITION FEATURES

ENGINE

MF5M.105: 105 Max Engine HP, 100 Rated Engine HP, 80 PTO HP
MF5M.115: 115 Max Engine HP, 110 Rated Engine HP, 90 PTO HP
MF5M.135: 135 Max Engine HP, 130 Rated Engine HP, 105 PTO HP
MF5M.145: 145 Max Engine HP, 140 Rated Engine HP, 110 PTO HP

4.4L 4-Cylinder AGCO POWER™
EPA Tier 4, CARB Certified
Air Cleaner: Dual Element Dry Type
Air Cleaner Intake, Under Hood
Vertical Exhaust
Cooling System: Antifreeze 50/50 Mix
Cold Start Aid: Intake Heater
52 Gallon Fuel Tank with Guard

POWERTRAIN

Transmission

- 12 x 12 Transmission (6 Gears, 2 Ranges, 25 MPH)
- De-Clutch Button on Main Gear Lever
- Power Control Reverse Lever

Rear Axle

Flanged Rear Axle
Inboard Planetary Final Drives
Push-Button Operated Mechanical Differential Lock

Brakes

Hydraulic Oil-Cooled Disc Brakes
Hook and Lever Parking Brake

PTO

Independent PTO:

- 540/540E/1000 RPM Flanged PTO
- 6 and 21 Spline Shafts (1.375 in. Diameter)
- Independent Wet Disc Clutch
- Electro-Hydraulic Engagement

Front Axle

4WD Power Front Axle
Dana 720 Center Driveline with Open Differential
Hydraulically Activated Differential Lock
Push-Button 4WD Engagement

HYDRAULICS

Open Center System with Engine-Driven Gear Pump
26 GPM (98 L/min) Combined Flow
2 Mechanical Controlled Spool Valves (2 x DA KO FL)

HITCH

Category 2 Rear Linkage with Telescoping Ball Ends (**5M.105, 5M.115**)
Category 3/2 Rear Linkage with Telescoping Ball Ends (**5M.135, 5M.145**)
Lift Capacity @ 24" - 7,716 lbs (3,500 kg)
Electronic 3-Point Linkage and Draft Controls
Adjustable Rear Links
Telescoping Stabilizers
Category 2 Swinging Drawbar with 250/400/500mm Positions and Clevis

WHEELS AND TIRES

5M.105 / 5M.115: F: Trelleborg 380/85R24 (14.9R24) R1
R: Trelleborg 460/85R34 (18.4R34) R1
5M.135 / 5M.145: F: Trelleborg 380/85R28 (14.9R28) R1
R: Trelleborg 460/85R38 (18.4R38) R1

ELECTRICAL

12 Volt DC, Negative Ground
Intake Pre-Heater
High Capacity Wet-Charge SAE 720cc Battery
80 Amp Alternator
Keyed Ignition with Safety Start
Keyed Engine Shutoff
Engine RPM Memory Switch

LIGHTING

4 Headlights
2 Mid-Mounted Halogen Worklights
1 Rear-Mounted Halogen Worklight
Rear Brake Lights

INSTRUMENTS

Instrument Panel with Performance Monitor
Analog Engine Tachometer
Analog Fuel Gauge
Analog Engine Temperature Indicator
Digital Transmission Display
Digital Hour Meter
Operation and Service Lights

OPERATOR ENVIRONMENT

Flat Floor Platform with Full Rubber Floor Mat
Rubber Isolator Mounts
Hand Rails with Glass Heat Shields
Mechanical Hitch Lift / Lower
External 3-Point Lift Control on Left Hand Side of Fender
2-Post Folding ROPS
Tilt Steering Column
Mechanical Spring Suspension Seat with Armrests
Retractable Seat Belt
Cup Holder
Suspended Foot Pedals
Electronic Hand and Foot Throttle
Left Hand and Right Hand Side Steps
Fender-Mounted Controls
Electronic Lift Control (Left Hand Side)
Electronic PTO Start / Stop Control (Left Hand Side)

OTHER STANDARD FEATURES

One Piece Tilting Hood
Rear Fender Side Extensions
Fuel Tank Guard
Toolbox
SMV Sign
Rear Oil Catcher
Water Separator
Front Weight Frame without Tow Pin

MF5M.135 / MF5M.145 WITH 12X12 TRANSMISSION - NOT FOR SALE IN STATE OF NEBRASKA

DECEMBER 2025

Model Number: MF5M.115D
Model Year: 2026

QQ Number: QQ-1063147
Serial Number: AGCMH060ATB019001

Invoice Number: 92346777
Order Number: 1986565

Dealership Name: Pomeroy Ranch Equipment LLC
Location: Kerens (630525)

5M Series



(F.O.B. PORT OF ENTRY)

CAB EDITION FEATURES

ENGINE

MF5M.105: 105 Max Engine HP, 100 Rated Engine HP, 80 PTO HP
MF5M.115: 115 Max Engine HP, 110 Rated Engine HP, 90 PTO HP
MF5M.135: 135 Max Engine HP, 130 Rated Engine HP, 105 PTO HP
MF5M.145: 145 Max Engine HP, 140 Rated Engine HP, 110 PTO HP

4.4L 4-Cylinder AGCO POWER™
EPA Tier 4, CARB Certified
Air Cleaner: Dual Element Dry Type
Air Cleaner Intake, Under Hood
A-Pillar Exhaust with Heat Shield
Cooling System: Antifreeze 50/50 Mix
Cold Start Aid: Intake Heater
52 Gallon Fuel Tank with Guard

POWERTRAIN

Transmission

- 12 x 12 Transmission (6 Gears, 2 Ranges, 25 MPH) or 16 x 16 Transmission (4 Gears, 4 Ranges, 25 MPH)
- De-Clutch Button on Main Gear Lever
- Power Control Reverse Lever

Rear Axle

Flanged Rear Axle
Inboard Planetary Final Drives
Push-Button Operated Mechanical Differential Lock

Brakes

Hydraulic Oil-Cooled Disc Brakes
Hook and Lever Parking Brake

PTO

Independent PTO:

- 540/540E/1000 RPM Flanged PTO
- 6 and 21 Spline Shafts (1.375 in. Diameter)
- Independent Wet Disc Clutch
- Electro-Hydraulic Engagement

Front Axle

4WD Power Front Axle
Dana 720 Center Driveline with Open Differential
Hydraulically Activated Differential Lock
Push-Button 4WD Engagement

HYDRAULICS

Open Center System with Engine-Driven Gear Pump
26 GPM (98 L/min) Combined Flow
2 Mechanical Controlled Spool Valves (2 x DA KO FL)

HITCH

Category 2 Rear Linkage with Telescoping Ball Ends (**5M.105, 5M.115**)
Category 3/2 Rear Linkage with Telescoping Ball Ends (**5M.135, 5M.145**)
Lift Capacity @ 24" - 7,716 lbs (3,500 kg)
Electronic 3-Point Linkage and Draft Controls
Adjustable Rear Links
Telescoping Stabilizers
Category 2 Swinging Drawbar with 250/400/500mm Positions and Clevis

WHEELS AND TIRES

5M.105 / 5M.115: F: Trelleborg 380/85R24 (14.9R24) R1
R: Trelleborg 460/85R34 (18.4R34) R1
5M.135 / 5M.145: F: Trelleborg 380/85R28 (14.9R28) R1
R: Trelleborg 460/85R38 (18.4R38) R1

ELECTRICAL

12 Volt DC, Negative Ground
Intake Pre-Heater
High Capacity Wet-Charge SAE 720cc Battery
120 Amp Alternator
Keyed Ignition with Safety Start
Keyed Engine Shutoff
Engine RPM Memory Switch
7-Pin Trailer Connector
One Electrical Outlet in Cab
LIGHTING
4 Headlights
2 Mid-Mounted Halogen Worklights
2 Cab-Mounted Halogen Rear Worklights
2 Cab-Mounted Halogen Front Worklights
Rear Brake Lights

INSTRUMENTS

Instrument Panel with Performance Monitor
Analog Engine Tachometer
Analog Fuel Gauge
Analog Engine Temperature Indicator
Digital Transmission Display
Digital Hour Meter
Operation and Service Lights

OPERATOR ENVIRONMENT

Standard Cab Roof
Manual Climate Control
Left Hand and Right Hand Side Entry Doors with Handrails
Left Hand and Right Hand Side Steps
Rubber Floor Mat
Telescopic Large Side Mirrors
Internal Mirror
Tilt and Telescoping Steering Column
Air Suspended Swiveling Seat with Armrests
Retractable Seat Belt
Instructor's Seat with Seat Belt
Cup Holder
Suspended Foot Pedals
Electronic Hand and Foot Throttle
Front and Rear Wiper / Washer
Two Audio Speakers and Antenna (Less Radio)
Fender-Mounted Controls (Dyna-4)
Electronic Lift Control (Left Hand and Right Hand Side)
Electronic PTO Start / Stop Control (Left Hand Side)

OTHER STANDARD FEATURES

One Piece Tilting Hood
Rear Fender Side Extensions
Fuel Tank Guard
Toolbox
SMV Sign
Rear Oil Catcher
Water Separator
Front Weight Frame without Tow Pin

MF5M.135 / MF5M.145 WITH 12X12 TRANSMISSION - NOT FOR SALE IN STATE OF NEBRASKA

DECEMBER 2025

Model Number: MF5M.115D
Model Year: 2026

QQ Number: QQ-1063147
Serial Number: AGCMH060ATB019001

Invoice Number: 92346777
Order Number: 1986565

Dealership Name: Pomeroy Ranch Equipment LLC
Location: Kerens (630525)



MASSEY FERGUSON

5M Series

(F.O.B. PORT OF ENTRY)

LOADER FEATURES

MF 941X Non-Self Leveling

- 148 in. (3700mm) Max Lift Height at Pivot Pins
- 3,650 lb. (1650kg) Lift Capacity to Max Lift Height at Pivot Pins
- **2,220 lb. (1010kg)** Lift Capacity to Max Lift Height, 31.5 in. (800mm) Forward of Pivot Pins
- 4,550 lb. (2070kg) Lift Capacity to 59 in. (150mm) Lift Height at Pivot Pins
- 3,350 lb. (1520kg) Lift Capacity to 59 in. (150mm) Lift Height, 31.5 in. (800mm) Forward of Pivot Pins

MF 946X Mechanical Self Leveling

- 148 in. (3700mm) Max Lift Height at Pivot Pins
- 3,000 lb. (1360kg) Lift Capacity to Max Lift Height at Pivot Pins
- **3,500 lb. (1590kg)** Lift Capacity to Max Lift Height, 31.5 in. (800mm) Forward of Pivot Pins
- 3,790 lb. (1720kg) Lift Capacity to 59 in. (150mm) Lift Height at Pivot Pins
- 3,770 lb. (1710kg) Lift Capacity to 59 in. (150mm) Lift Height, 31.5 in. (800mm) Forward of Pivot Pins
- Construction
 - ▶Welded Box Section Loader Beams with Internally Routed Hydraulic Hoses for Neat Concealment and Protection
 - ▶Tough and Durable Powder Coat Finish Ensuring Long Life
 - ▶Low Placement of the Cross Tube Does Not Block the Tractor Lights
 - ▶A tapered Design with the Lowest Knee Placement on the Market Makes for Superb Side Visibility
- Quick Detaching
 - ▶Simply Place the Implement on the Ground, Lower the Parking Stands, Unlatch the Pins and Disconnect the Hydraulic Connections Between the Loader and Tractor
 - ▶For Faster Hydraulic Connection, a Simple Action Multicoupler is Available
- Versatile Options
 - ▶SoftDrive Loader Suspension Reduces Stresses on the Loader, Tractor, as Well as the Operator
 - ▶Third Function Diverter to Utilize a Grapple or Bale Squeeze

FL3723 Non-Self Leveling

- 149.3 in. (3790mm) Max Lift Height at Pivot Pins
- 4,520 lb. (2050kg) Lift Capacity to Max Lift Height at Pivot Pins
- **2,840 lb. (1290kg)** Lift Capacity to Max Lift Height, 31.5 in. (800mm) Forward of Pivot Pins
- 5,090 lb. (2310kg) Lift Capacity to 59 in. (150mm) Lift Height at Pivot Pins
- 3,790 lb. (1720kg) Lift Capacity to 59 in. (150mm) Lift Height, 31.5 in. (800mm) Forward of Pivot Pins

FL3819 Mechanical Self Leveling

- 149.3 in. (3790mm) Max Lift Height at Pivot Pins
- 3,770 lb. (1710kg) Lift Capacity to Max Lift Height at Pivot Pins
- **4,230 lb. (1920kg)** Lift Capacity to Max Lift Height, 31.5 in. (800mm) Forward of Pivot Pins
- 4,250 lb. (1930kg) Lift Capacity to 59 in. (150mm) Lift Height at Pivot Pins
- 4,280 lb. (1940kg) Lift Capacity to 59 in. (150mm) Lift Height, 31.5 in. (800mm) Forward of Pivot Pins
- Construction
 - ▶Welded C Section Loader Beams with Internally Routed Hydraulic Hoses for Neat Concealment and Protection
 - ▶Tough and Durable Powder Coat Finish Ensuring Long Life
- Lock and Go System
 - ▶Simple 5-Step Process for Attachment/Detachment Requiring No Tools and Rigid Support Legs
- Easy and Fast Hydraulic Connection
 - ▶Connection of the Tractor and Loader is Made Easy by Compact Design of Flat Face Couplings
 - ▶For Faster Hydraulic Connection, Simple Action Multicouplers are Available
- SoftDrive
 - ▶Shock Absorption System that Reduces Stresses on the Loader, Tractor, as Well as the Operator
 - ▶Hidden and Protected inside the Cross Tube, SoftDrive can be Electronically Activated When you Need It

DECEMBER 2025

Model Number: MF5M.115D
Model Year: 2026

QQ Number: QQ-1063147
Serial Number: AGCMH060ATB019001

Invoice Number: 92346777
Order Number: 1986565

Dealership Name: Pomeroy Ranch Equipment LLC
Location: Kerens (630525)